

Protex - Scratch Finish Superlative Texture

The Product

Eureka Paints Protex Scratch Finish Texture is a acrylic / synthetic, semi viscous paste containing quartz, aggregates, acrylic polymers, minerals, specially formulated to withstand varying climate conditions & provide a long lasting elegant look to the surface.

Key Features

- Eureka Paints Protex Scratch Finish Texture gives a very high aesthetic as well as protection value.
- Extra thickness imparts toughness to the surface thus making it water resistance.
- Hides surface undulations & existing cracks.
- It also gives an opportunity to create different designs, viz. vertical, zig zag, circular, rain drop, etc.
- Being Polymer based the strength is good thus making it highly durable & maintenance free.
- Non Toxic & Non Flammable.
- It comes in different thickness, viz. 1mm, 2mm, 3mm.

Substrate Suitability




Eureka Paints Protex Scratch Finish Texture can be easily applied on surfaces like plaster, concrete, gypsum, wood or any other kind of surfaces, adhering to the suggested application procedures.

How To Use

Surface Preparation

- Clean the surface with sharp stone and wire brush to remove any paint and all loose particles or cement water completely and thoroughly.
- Also ensure that any previous growth of fungus, algae or moss is properly removed & cleaned with water.
- On the fungus affected area apply one coat of Bio wash or Eureka Penetrating Sealer.
- All the existing leakages from inside should be treated in proper manner.
- One coat of Eureka EWP - Exterior Primer is recommended for Pre painted surface

Application System

Product	Application Tool	Thinner	Dilution % (by vol)	Touch Dry	Recoat*
Priming 1st coat Eureka Paints EWP - Exterior Waterbase Acrylic Primer (For Pre Painted Surface)	 Brush,  Spray	Water Water	65-70% 90-100%	1 hr 1 hr	4 hrs 4 hrs
Protex - Scratch Finish Superlative Texture 2 coats of recommended paint system	 Trowel	Water if required	Max 5% for workability	4 hrs	12 hrs

* Recoat period is quoted for 25° C at 50% relative humidity - may vary under different conditions.

Technical Data

1)	Covering**	2.5 - 3.00 sft per kg
2)	Drying Time	Touch Dry 4 Hrs Hard Dry 12 Hrs
3)	Condition in can	Ready to use paste
4)	Thickness Standard	2mm
5)	Recommended DFT per coat	2mm
6)	Spreading	2.5 - 3.00 sft per kg at the DFT of 2mm
7)	Specific Gravity	Kg/ltr. 1.70 +/- 0.05
8)	Viscosity	330
9)	PH value	8 to 9
10)	Hardness	4H
11)	Shelf Life	6 months when stored in cool & dry place in original sealed container
12)	Top Coat	Compatible to all the existing top coating systems (viz. Acrylic Emulsions, Tex, Metallic, etc)

**Covering mentioned depends on the condition of the surface & method of application

Precautions

- Stir Well & strain before use
- Thinning is not advisable
- Do not apply to surface that are subject to continuous seepage of dampness



Pack Sizes & Shade Range

5kg, 20kg Tin
30kg HDPE Bag

Shade - Base

Regd. Off. : 5 Meghdoot, 2nd Floor, Plot No. 283, Flank Road,
Opp. S R Mehta (Kikabhai) Hospital, Sion (E), Mumbai - 400022.

Manufactured at : Eureka Paints, Unit No.A 743,TTC Industrial Area,
MIDC Village Khairne, Near Ruchit Palace Hotel, Navi Mumbai.

Customer Care :

Phone : +91-22-24096182 / 24070437 | Mobile : +91-9867466661
Email : info@eurekapaints.in | Web : www.eurekapaints.in